

Super-Tek Acrylic Grout Additive
Acrylic additive for enhancing Portland cement grout.

1. MANUFACTURER

Super-Tek Products, Inc.
25-44 Borough Place
Woodside, NY 11377 USA
Telephone: (718) 278-7900
Fax: (718) 204-6013
Fax back on Demand: (718) 278-5311
Internet: www.super-tek.com

2. PRODUCT DESCRIPTION

An acrylic additive for enhancing Portland cement grouts for interior or exterior installations of ceramic, porcelain, quarry, marble, pavers and other natural stone tiles on floors and walls.

- Increases grout bond to tile and substrate
- Improves color uniformity and retention
- Enhances stain resistance
- Improves freeze-thaw stability
- Interior/exterior use

Note: When mixed in place of water, creates the enhanced characteristics of a polymer-modified grout exceeding ANSI A118.6 standards.

3. INSTALLATION

For proper performance, tile must be grouted in accordance with Manufacturer's instructions.

SURFACE PREPARATION: All joints to be grouted must be clean and free of dust, grease, sealants and foreign matter.

MIXING: Shake or stir product before using. Acrylic Grout Additive is designed to replace "all" of the mixing water normally used when mixing grout. Pour approximately 2/3 of the bottle into a clean, dry mixing pail. Add the dry, powdered grout and stir. Add as much additional liquid as needed to obtain the desired consistency. If additional dilution is required, a small quantity of water may be added.

COVERAGE: The 25-ounce jug mixes directly with 8.8 pounds of Versa-Tile Floor Grout (sanded joint filler) or 5 pounds of Dry-Set Wall Grout. The half-gallon jug mixes with 25 pounds of Versa-Tile Floor Grout or 8.8 pounds of Dry-Set Wall Grout. The one-gallon jug mixes with 50 pounds of Versa-Tile Floor Grout or 25 pounds of Dry-Set Wall Grout.

APPLICATION: See grout package for detailed instructions on how to grout.

WARNING! EYE AND SKIN IRRITANT. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

4. COVERAGE:

See grout manufacturer's coverage chart.

5. PACKAGING:

Packaged in 25-ounce, half-gallon, and 1-gallon plastic jugs. Color: White.

6. SHELF LIFE:

Store in original, tightly sealed container at room temperature. PROTECT FROM FREEZING. Product is freeze-thaw stable but freezing should be avoided whenever possible. Excessive cycling or prolonged frozen states can damage the adhesive. Shelf life is one year from date of manufacture.

7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for its intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

8. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900

FAX: (718) 204-6013

To receive product information or Material Safety Data Sheets via fax 24 hours 7 days, call: (718) 278-5311