

Super-Tek Clear Set

Ceramic Wall & Floor Tile Adhesive For interior installations of ceramic tile on walls and floors.

1. MANUFACTURER

Super-Tek Products, Inc.

25-44 Borough Place

Woodside, NY 11377 USA

Telephone: (718) 278-7900

Fax: (718) 204-6013

Fax-back on Demand: (718) 278-5311

Internet: www.super-tek.com

2. PRODUCT DESCRIPTION

A latex-based adhesive for installing vinyl composition tile (VCT). It provides excellent workability with a quick, strong bond. It is both water resistant and plasticizer migration resistant. Adhesive appears clear when dry.

- High Bond Strength
- Excellent Open Time
- Dries clear (chalk lines are visible)
- Residential and commercial applications.

3. INSTALLATION

APPROVED SUBSTRATES: Interior floor surfaces such as plywood, underlayment grade hardboard, association grade particleboard, wood floors (sanded), resilient tile (non-cushioned and wax free), concrete (do not use on or below grade where excessive moisture, vapor, alkali or hydrostatic pressure exists). Carefully read and follow all instructions provided by the floor covering manufacturer. Before installation begins measure and mark the floor as necessary.

PLEASE NOTE: Allow installation area, VCT and adhesive to acclimate to a temperature of 68°F for 24 hours before installation.

PREPARATION: Surface must be clean, dry, rigid, smooth, and free of all foreign matter. Remove loose tiles, dust, dirt, wax, paint, etc. Doubtful surfaces can be sanded and/or primed to enhance adhesion. Tongue-and-groove sub-floors wider than 3" should be covered with underlayment sheeting. Patch all cracks, seams, or irregularities. Concrete must be fully cured, dry, and free of excessive moisture and alkalinity. If doubt exists about excessive moisture it may be checked by placing a rubber mat on the floor. Wait 24 hours, then lift mat and examine concrete underneath. If it is dry, proceed with floor covering installation. Note: It is the responsibility of the USER to properly prepare the surface or backing before the application of the adhesive. If doubt exists check with SELLER or MANUFACTURER.

APPLICATION: Apply a smooth, uniform coating of adhesive to the floor. Allow adhesive to dry until tacky and transparent (approximately 30 minutes depending on temperature and humidity). Before applying tiles test for sufficient tack by gently running a finger over the adhesive. If adhesive does not transfer to finger, tiles may be applied. After tiles are placed in desired position, firmly press the surface with a linoleum roller or rolling pin to insure a firm bond and the expulsion of all air bubbles. Work from the center out, towards the edges, pushing in both directions. Tile may be installed up to 24 hours after adhesive has set.

CURING: Protect installation from exposure to water, heavy traffic, and freezing temperatures for a minimum of 72 hours.

CLEAN UP: Remove excess wet adhesive from tools, surface of tiles, etc. using water-dampened cloth or sponge. Dried adhesive may be removed using mineral spirits or other solvents. Exercise due care and follow all manufacturers' precautions when using solvents.

WARNING! EYE AND SKIN IRRITANT. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

4. COVERAGE:

Brush, 250-300 square feet per gallon.

Roller, 200-250 square feet per gallon.

Trowel, 150-200 square feet per gallon (using 1/16" x 1/16" x 1/16" square notch).

5. PACKAGING:

Quart, 1-gallon, 2-gallon, 3.5-gallon, & 5-gallon pails. Color: Off-White.

6. SHELF LIFE:

Store in original, tightly sealed container at room temperature. **PROTECT FROM FREEZING.** Product is freeze-thaw stable but freezing should be avoided whenever possible. Excessive cycling or prolonged frozen states can damage the adhesive. Shelf life is one year from date of manufacture.

7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for its intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

8. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900 ext. 111

Fax: (718) 204-6013

To receive product information or Material Safety Data Sheets via fax 24 hours 7 days, call: (718) 278-5311