

## Super-Tek Glue N Grout

Bright white, ready mixed adhesive for interior installations of ceramic tile and mosaics on walls.

### 1. MANUFACTURER

Super-Tek Products, Inc.

25-44 Borough Place

Woodside, NY 11377 USA

Telephone: (718) 278-7900

Fax: (718) 204-6013

Fax back on Demand: (718) 278-5311

Internet: [www.super-tek.com](http://www.super-tek.com)

### 2. PRODUCT DESCRIPTION

Bright white, ready mixed adhesive and grout for 4 ¼"x4 ¼" ceramic tile and mosaics. Meets or exceeds ANSI 136.1 Type II Adhesive for interior areas "having light service, dry or limited water exposure".

- Ready-Mixed Formula
- Ideal for small repairs
- Easily tinted with universal colorant
- Dry Area Installations
- Meets or Exceeds ANSI A136.1 Type II

### 3. INSTALLATION

APPROVED SUBSTRATES: Concrete block, plumb and true masonry, gypsum board, and cured plaster.

DO NOT USE OVER: Hardwood, plywood, existing tile, cement backer board, masonite, chipboard, flake-board, presswood, asbestos board, vinyl flooring, luan plywood, OSB, metal, gypsum based levelers, glass, plastic, wallpaper, sandy brown-coat plaster, fresh plaster with high moisture content or other similarly unstable substrates.

PLEASE NOTE: 1) DO NOT set bathroom accessories or grab bar fixtures with this adhesive, use Super-Tek's Super-Fixset. 2) Store tile and adhesive at approximately 68°F (21°C) for a period of 24 hours prior to use. 3) For areas requiring "Prolonged Water Resistance", such as tub surrounds or shower walls, use Super-Tek's Dual Purpose or Platinum Dual Purpose Adhesive that conform to ANSI 136.1 Type I Adhesive. It is the responsibility of the USER to properly prepare the subsurface or backing before application of the adhesive. If doubt exists check with SELLER or MANUFACTURER.

INSTALLATION: All installations must be set in accordance with the most recent publication of the Tile Council of America's "Handbook For Ceramic Tile Installations" and the following guidelines.

#### APPLICATION:

Application as adhesive-All surfaces must be clean and free of dust, grease, wax, and foreign matter. Using pressure, apply a thin skim coat with flat edge of trowel. Then using the proper sized notched trowel apply a second coat to form ridges. Trowel only in an area that can be tiled before the adhesive skins over (20-30 minutes). If adhesive skins over, remove and apply fresh adhesive. Apply dry tiles with pressure and a slight twisting motion. Immediately beat tiles in to ensure maximum contact and bond. After setting several tiles, remove one or two and inspect, making sure tile backs are 100% covered with adhesive. Back buttering of tiles may be necessary to insure 100% coverage. Do not use at temperatures below 45°F (7°C) or above 95°F (35°C).

Application as grout: Pressure product into open joints using rubber float trowel, squeegee, or fingers (rubber gloves recommended) Remove as much excess as possible, then allow grout to set. After setting remove grout film by wiping tiles diagonally across the joints using a damp, but well rung sponge. Keep washing to a minimum but rinse and ring sponge as often as needed. Continue wiping until face of tile is clean and joints are thin, smooth and uniform. Grout will firm within the hour and a haze will appear over face of tiles. Final step - clean and polish tiles using clean, dry, cloth. Note: Do Not allow haze to remain on face of tiles, it must be completely removed during "Final Step".

How to tint: Add water-based or universal colorant. Stir thoroughly, until uniform.

CURING: Jobsite temperature must remain between 45°F and 95°F for a minimum of 72 hours after installation.

CLEAN UP: Remove excess wet adhesive from face of tile using water dampened cloth or sponge.

WARNING! EYE AND SKIN IRRITANT. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

#### 4. COVERAGE:

Approximate coverage:

Quart covers 38-40 square feet or standard 4 ¼"x 4 ¼" ceramic wall tile, or 12-16 square feet of mosaic tile.

#### 5. PACKAGING:

Quarts. Color: Bright White.

#### 6. SHELF LIFE:

Store in original, tightly sealed container at room temperature. PROTECT FROM FREEZING. Product is freeze-thaw stable but freezing should be avoided whenever possible. Excessive cycling or prolonged frozen states can damage the adhesive. Shelf life is one year from date of manufacture.

#### 7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for it's intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

#### 8. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900 ext. 111

FAX: (718) 204-6013

To receive product information or Material Safety Data Sheets via fax 24 hours 7 days, call:(718) 278-5311