

Super-Tek Level-Mate

Quick setting, gypsum-based skim coat and patching compound used prior to installing resilient flooring and carpet.

1. MANUFACTURER

Super-Tek Products, Inc.

25-44 Borough Place

Woodside, NY 11377 USA

Telephone: (718) 278-7900

Fax: (718) 204-6013

Fax back on Demand: (718) 278-5311

Internet: www.super-tek.com

2. PRODUCT DESCRIPTION

A quick setting, gypsum-based skim coat and patching compound for filling low spots, cracks and holes to form an even surface in preparation for sheet vinyl, V.C.T. and carpet installations. Install flooring in as little as 1 1/2 to 2 hours. Can also be used for patching and leveling in drywall and plaster walls.

- Use over concrete and wood substrates
- Levels from featheredge to 1/2"
- Install flooring in as little as 1 - 1 1/2 hours
- Interior use

3. INSTALLATION

APPROVED SUBSTRATES: Properly prepared concrete, concrete block, plumb and true masonry, exterior grade plywood (interior floors only), drywall and plaster walls.

DO NOT USE OVER: Hardwood, existing tile, cement backer board, masonite, chipboard, flakeboard, presswood, asbestos board, vinyl flooring, luan plywood, OSB, metal, glass, plastic, cutback adhesive residue, laminate counter tops, or other similarly unstable substrates.

PLEASE NOTE: 1) Not for use over concrete slabs on grade or where moisture migration is possible, use Super-Tek's Super-Flexcote or Super Skim/Patch instead.

MIXING: Add approximately 1 gallon of cool, clean water to 25 lbs. of Level-Mate and mix to a thick, paste-like consistency. Use slow speed bucket mixers or mortar box for mixing, do not use high-speed drills. Keep mix times to a minimum. Blend only long enough to attain a smooth, consistent mix. **DO NOT** slake or allow to stand. Mixture should be stirred occasionally during use, if mix thickens beyond use **DO NOT** add water and **DO NOT** retemper. Discard and mix fresh batch. Pot life is approximately 20-30 minutes depending on temperature and humidity.

APPLICATION: All surfaces must be clean and free of dirt, oil, grease, wax, and foreign matter. Concrete floors must be fully cured and free of curing compounds. If concrete is very dry or dusty, dampen concrete with water before applying Level-Mate. Using pressure, apply the initial coat with a broad putty knife or the flat edge of trowel to ensure good adhesion to substrate. Finish with a steel trowel immediately after completing application.

CURING: Jobsite temperature must remain between 45°F and 95°F for a minimum of 72 hours after installation.

WARNING! EYE AND SKIN IRRITANT. BREATHING DUST MAY CREATE LUNG CANCER RISK. CONTAINS CRYSTALLINE SILICA AND PORTLAND CEMENT.

Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

4. COVERAGE:

Level-Mate covers approximately 25-30 square feet at a thickness of 1/8", per 25 pound bag.

5. PACKAGING:

25 lb bags. Color: White.

6. SHELF LIFE:

Store bags in a cool, dry location out of direct sunlight. Do not store bags on the ground or on concrete. Protect bags from weather and freezing. Shelf life is one year from date of manufacture.

7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for it's intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

8. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900 ext. 111

FAX: (718) 204-6013

To receive product information or Material Safety Data Sheets via fax 24 hours 7 days, call: (718) 278-5311