

Super-Tek Perfect Seal  
Durable Siliconized Acrylic Caulk.

#### 1. MANUFACTURER

Super-Tek Products, Inc.  
25-44 Borough Place  
Woodside, NY 11377 USA  
Telephone: (718) 278-7900  
Fax: (718) 204-6013

#### 2. PRODUCT DESCRIPTION

Perfect Seal Caulk is an easy to use acrylic caulk formulated specifically to match 10 of Super-Tek's most popular grout colors. Perfect for creating a professional designer look. For use around tubs, showers, counter tops, backsplashes, thresholds and windows. Non-Sag formula allows for use on vertical installations

- Bonds to Most Surfaces
- Tough and Flexible
- Indoor or outdoor use
- Moisture, Mildew and UV resistant

#### 3. INSTALLATION

APPROVED SUBSTRATES: Properly prepared ceramic tile, stone, brick, concrete, wood, plaster, metal, glass, fiberglass, and high pressure laminates.

PLEASE NOTE: This product contains colorants that may stain some porous materials. Mask or protect these areas to protect from staining. Test an inconspicuous area first.

#### APPLICATION:

1. Surfaces must be clean and free of dust, dirt, oil and other foreign substances. Remove old caulk or sealants.
2. Cut tip to desired bead thickness.
3. Apply caulk bead by drawing tube towards you. Maintain pressure while applying.
4. Shape caulking within 20 minutes of application. Use wet finger or smooth wet sponge.

CURING: Jobsite temperature must remain between 45°F and 95°F for a minimum of 72 hours after installation.

CLEAN UP: Excess may be cleaned up with warm soapy water when fresh. Cured material can be cut or scraped away with a razor blade.

LIMITATIONS: Do not use at temperatures below 40 F. Not for use under water.

WARNING! EYE AND SKIN IRRITANT. BREATHING DUST MAY CREATE LUNG CANCER RISK. CONTAINS CRYSTALLINE SILICA AND PORTLAND CEMENT. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

#### 4. PACKAGING:

10.3 oz. Tube

#### 5. SHELF LIFE:

Store in original, tightly sealed container at room temperature. PROTECT FROM FREEZING. Product is freeze-thaw stable but freezing should be avoided whenever possible. Excessive cycling or prolonged frozen states can damage the adhesive. Shelf life is one year from date of manufacture.

#### 6. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for its intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

#### 7. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900 ext. 111

FAX: (718) 204-6013