

Super-Tek Super-Fixset

Fast Setting adhesive compound specifically formulated for installing ceramic fixtures.

1. MANUFACTURER

Super-Tek Products, Inc.

25-44 Borough Place

Woodside, NY 11377 USA

Telephone: (718) 278-7900

Fax: (718) 204-6013

Fax back on Demand: (718) 278-5311

Internet: www.super-tek.com

2. PRODUCT DESCRIPTION

A rapid-setting ceramic fixture mounting compound.

- Sets in 10 minutes
- Water-resistant
- Powder to be mixed with water

3. INSTALLATION

APPROVED SUBSTRATES: Properly prepared concrete, concrete block, plumb and true masonry, gypsum board, and cement backer board.

DO NOT USE OVER: Hardwood, existing tile, masonite, chipboard, flakeboard, presswood, asbestos board, vinyl flooring, luan plywood, OSB, metal, gypsum based levelers, glass, plastic, cutback adhesive residue, laminate counter tops, or other similarly unstable substrates.

MIXING: Using a clean bucket or pail, simply sprinkle Super-Fixset into a small quantity of water. Stir gently with minimum agitation, to obtain putty consistency. Sprinkle additional powder as needed to obtain a thick, paste-like consistency.

APPLICATION: Spread a generous amount of compound on back of bathroom fixture. Work quickly. Squeeze fixture into place allowing excess compound to ooze. Wipe up excess quickly with damp sponge. Hold fixture in position until compound begins to set. This will occur in a few minutes. Once the material has set, the fixture will harden in place and Super-Fixset will reach its full strength in approximately 20 minutes.

CLEAN UP: Remove excess adhesive from tile or tools immediately using water dampened cloth or sponge. Petroleum solvents will assist if adhesive has cured.

WARNING! EYE AND SKIN IRRITANT. BREATHING DUST MAY CREATE LUNG CANCER RISK. CONTAINS CRYSTALLINE SILICA AND PORTLAND CEMENT. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

4. PACKAGING:

Available in 5lb. poly bag. Color: White.

5. SHELF LIFE:

Store in original, tightly sealed container at room temperature. Shelf life is one year from date of manufacture.

6. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for it's intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

7. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900

FAX: (718) 204-6013

To receive product information or Material Safety Data Sheets via fax 24 hours 7 days, call: (718) 278-5311