

Formulated Solutions Super-Seal

1. MANUFACTURER

Formulated Solutions, LLC.
25-44 Borough Place
Woodside, NY 11377 USA
Telephone: (718) 267-6380
Fax: (718) 204-6013
Internet: www.formulatedsolutions.net

2. PRODUCT DESCRIPTION

Waterproofing cement mix coating for masonry and concrete.

3. INSTALLATION

MIXING: Add water to mixing container and gradually add powder to bring consistency of mix to a heavy batter (approximately one gallon of water per 25 lbs.). Stir to a uniform consistency. Allow material to slake for fifteen minutes, then restir. A small amount of water may be added to adjust consistency. Under normal conditions pot life exceeds 1-1/2 hours. If latex additive is desired, add SUPER-CRYL instead of water; follow normal mixing directions.

APPLICATION: All surfaces must be clean and free of dust, grease, wax, and foreign matter. Dampen surface immediately ahead of application. Apply with tampico fiber brush or equal. Brush a thick layer onto wall and level it out. If wall becomes dry or Super-Seal is pulling, redampen wall. Two coats are recommended for normal waterproofing requirements. Allow 24 hours drying between coats. Again, redampen first coat before applying second coat. For severe water conditions apply second coat by trowel at a minimum coverage of 12 lbs. of Super-Seal per square yard. When troweling, add approximately one gallon (11 to 12 lbs.) of clean, fine white silica sand to every 25 lbs. of Super-Seal. All holes, pores, voids, etc. must be completely filled and sealed. The amount of material used will differ with various substrates, different application techniques, and the texture of the finish desired. Do not use at temperatures below 50°F (10°C) or above 95°F (35°C).

CURING: Under average drying conditions (70 °F (21° C) and 55% R.H.) Super-Seal will dry in 24 hours. Lower temperatures and/or high humidity will extend the drying time required for this product. It is the users responsibility to make sure Super-Seal is properly cured before proceeding.

CLEAN UP: Remove excess Super-Seal from tools using water dampened cloth or sponge.

LIMITATIONS: Do not apply to frozen surfaces. Do not apply if temperature is below 50°F (10° C) or will fall below 50°F (10° C) within 24 hours after application. Protect from rain for 24 hours. Do not apply over 1/4" (6.4 mm) thick.

WARNING! EYE AND SKIN IRRITANT. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

4. COVERAGE:

Approximate coverage:
50-55 sq. ft. / bag

5. PACKAGING:

50 lb bag. Color: White & Grey.

6. SHELF LIFE:

One year from date of manufacture when stored in original packaging in a dry, ventilated place. Exposure to moisture will shorten the shelf life.

7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for its intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

8. TECHNICAL ASSISTANCE

Information is available by calling Formulated Solutions:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 267-6380 ext. 111

FAX: (718) 204-6013