

Formulated Solutions Super-Stuccote

1. MANUFACTURER

Formulated Solutions, LLC.
25-44 Borough Place
Woodside, NY 11377 USA
Telephone: (718) 267-6380
Fax: (718) 204-6013
Internet: www.formulatedsolutions.net

2. PRODUCT DESCRIPTION

High performance Portland cement decorative stucco mortar.

3. INSTALLATION

MIXING: Add water (approximately 1 1/2 gallons of water per 50 lbs.) to mixing container and gradually add powder to bring mix to a uniform consistency. Allow material to slake for fifteen minutes, then restir. A small amount of water may be added to adjust consistency. Under normal conditions pot life exceeds 1-1/2 hours. If latex additive is desired, add SUPER-CRYL instead of water; follow normal mixing directions.

APPLICATION: All surfaces must be clean and free of dust, grease, wax, and foreign matter. Ensure that all surfaces are smooth and free of any irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Just prior to application dampen all surfaces and avoid saturation. Apply with hawk and trowel a thick layer onto wall and level it out. Allow 24 hours drying between coats. Again, redampen first coat before applying second coat. Do not use at temperatures below 50°F (10°C) or above 95°F (35°C).

CURING: Under average drying conditions (70 °F (21° C) and 55% R.H.) Super-Stuccote will dry in 24 hours. Lower temperatures and/or high humidity will extend the drying time required for this product.

CLEAN UP: Remove excess Super-Stuccote from tools using water dampened cloth or sponge.

LIMITATIONS: Do not apply to frozen surfaces. Do not apply if temperature is below 50°F (10° C) or will fall below 50°F (10° C) within 24 hours after application. Protect from rain for 24 hours. Do not apply over 1/4" (6.4 mm) thick.

WARNING! EYE AND SKIN IRRITANT. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

4. COVERAGE:

Approximate coverage:
40-50 sq. ft. / bag

5. PACKAGING:

50 lb bag. Color: White & Grey.

6. SHELF LIFE:

One year from date of manufacture when stored in original packaging in a dry, ventilated place. Exposure to moisture will shorten the shelf life.

7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for its intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

8. TECHNICAL ASSISTANCE

Information is available by calling Formulated Solutions:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 267-6380 ext. 111

Fax: (718) 204-6013