

SUPER SCREED

Fast-setting, premixed, polymer-modified, hydraulic cement-based mortar for concrete repairs and subfloor preparation work.

1. MANUFACTURER

Super-Tek Products, Inc.

25-44 Borough Place, Woodside, NY 11377

Telephone #: 718-278-7900

Emergency Phone #: 718-278-7900

Generic ID: One Component Polymer-Modified Cement Based Patching Compound

Product Identity: Super-Screed

Date Prepared: 8/1/00

2. PRODUCT DESCRIPTION:

Fast-setting, premixed, polymer-modified, hydraulic cement-based mortar for concrete repairs and subfloor preparation work. Mix with water only. Allows floor covering (vinyl, wood, rubber, linoleum, carpet, etc.) to be installed after 24 hours. Ceramic tile and natural stone flooring can be installed after only 3 to 4 hours. The product can be applied from a minimum of ¼" to a maximum of 4".

3. SUBSTRATE:

Concrete (clean, rough textured and completely cured).

4. MIXING:

Add approximately 2 1/2 quarts of cool, clean water to 40 lbs. of Screed Mix. Use slow speed bucket mixers or mortar box for mixing, do not use high-speed drills. Allow mixture to slake (stand) for 2-3 minutes, and then remix before applying. Mixture should be stirred occasionally during use, do not retemper.

5. APPLICATION:

All surfaces must be clean and free of dust, grease, wax, and foreign matter. Do not use at temperatures below 45°F (7°C) or above 95°F (35°C).

PLEASE NOTE: 1) Not for exterior use. 2) Do not apply less than ¼" thick or exceed 4" thick. 3) Not for leveling large areas (use Super-Tek's Super-Level or Super-Flexcote leveling products for large areas). 4) Do not use to resurface concrete areas that will be left exposed or uncovered.

6. CURING:

Jobsite temperature must remain between 45°F and 95°F for a minimum of 72 hours after installation.

WARNING! EYE AND SKIN IRRITANT. BREATHING DUST MAY CREATE LUNG CANCER RISK. CONTAINS CRYSTALLINE SILICA AND PORTLAND CEMENT.

Avoid contact with eyes, skin and clothing. Avoid breathing dust. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult a physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Material Safety Data Sheet (MSDS) for this product.

7. NOTICE AND WARRANTY DISCLAIMER:

The MANUFACTURER has provided the enclosed Instructions/Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. It is the USER'S obligation to ensure that the product is suitable for it's intended use and that it is compatible with existing conditions or applications of other coincident or adjoining materials. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from

any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied.

8. TECHNICAL ASSISTANCE

Information is available by calling Super-Tek Products:

Mon. thru Fri. (Hours 8:00 AM to 4:30 PM EST)

Telephone: (718) 278-7900 ext. 111

FAX: (718) 204-6013

To receive product information or Material Safety Data Sheets via fax 24 hours 7 days, call: (718) 278-5311